



公差/General tolerances(mm)		D
0	>3	
~	>6	0.1/10
3	10	±2
~	18	
~	30	
±0.12	±0.18 ±0.22 ±0.26 ±0.31 ±0.37 ±0.57 ±0.80 ±0.93 ±1.05 ±1.15 ±1.60 ±2.20 ±2.50	

4	Nut	Steel	M3/Zn Plated
3	Housing2	PBT	UL94V-0
2	Pin	Copper	Sn Plated
1	Housing	PBT	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES
UL 标准/UL Standard:		B C D	
额定电压/电涌/Rated Voltage(V)/Current(A)		300/30 300/30 300/10	
EC 标准/IEC Standard:			
过压类别/Overvoltage Category/污染等级/Pollution Degree		III/3	III/2
额定电压/电流/Rated Voltage(V)/Current(A)		/	400/32
额定脉冲电压(KV)/Rate Impulse Voltage(KV)		/	4
间距/Pitch(mm)/线数范围/Poles		7.62/N=02~12P	/
使用温度范围/Operating temperature(°C)		-40~+105	/
符合RoHS环保要求/Conform to RoHS		Yes	/

MATERIAL:	
MAT NO.:	/
STATUS:	/
APPD:	
CHKD:	
DRFT: Cen/MZ 2020.06.04	
NAME:	DEGSON 宁波高松电子有限公司 NINGBO DEGSON ELECTRICAL CO., LTD
DRAWING NO.:	5EDGVM-7.62-C01
TYPE:	CUSTOMER DRAWING

DRFT:	Cen/MZ 2020.06.04	SCALE:	1.5:1 SHEET	REV	TO
SIZE:	A4				
REV	ECN	DESCRIPTION	DRFT	DATE	